
PRODUCT SPECIFICATION SHEET

Self-adhesive Numbers and Letters -

Packs of 0-9 & A-Z







Catalogue Text

- 6 sizes; cards of identical characters available A-Z (26 cards per pack) or 0-9 (10 cards per pack)
- Clean peel leaves no residue
- Black characters on yellow background

High visibility and simple to apply this range of numbers or letters are supplied on cards with all the same ch ar le

F3 0-9 and A-Z 19 x 14 16 36 F4 0-9 and A-Z 38 x 21 26 12 F5 0-9 and A-Z 56 x 21 50 12 F6 0-9 and A-Z 90 x 38 75 6 F7 0-9 and A-Z 130 x 45 100 5 F8 0-9 and A-Z 230 x 140 160 1

Label Size

Parameter	Specification	Test Method
Monomeric PVC soft film	0.075 mm	DIN 53 353
Tear Resistance (Min)	MD 19 N/mm ² : CD 17 N/mm ²	DIN 53 353
Tensile Strength (Min)	MD 30 N/mm ² : CD 28 N/mm ²	DIN 53 455
Elongation at break (Min)	MD 170% : CD 200%	DIN 53 455

Character Height

Characters/Card

haracters. They are simple to	Monomeric PVC soft film	0.075 mm	DIN 53 353
apply and can be quickly removed,	Tear Resistance (Min)	MD 19 N/mm ² : CD 17 N/mm ²	DIN 53 353
eaving no residue adhesive.	Tensile Strength (Min)	MD 30 N/mm ² : CD 28 N/mm ²	DIN 53 455
3	Elongation at break (Min)	MD 170% : CD 200%	DIN 53 455

Model

Material Specification

Facestock Material

Monomeric Soft PVC film, yellow or white gloss.

Adhesive

Copolymeric acrylates, solventfree, excellent resistance to UV-light and ageing.

Parameter	Specification	Test Method
Adhesive	0.08 mm Removable (R2)	
Peel adhesion	20mins. 4 N/25mm	FTM 1 on glass
Peel adhesion	24hrs 8 N/25mm	FTM 1 on glass
Application Temperature	+5°C min.	
Service Temperature	-30° C to +90° C	
Application on toys	Complies	EN 71/3
EC packaging directive	Complies (Heavy metals)	94/62/EC
Application non-fatty food	Approved	ISEGA Cert