

PRODUCT SPECIFICATION SHEET

Ticket Holders - Self-adhesive

25mm - 80mm



Catalogue Text

- For permanent locations
- Easy to update, pull forward front
- Clear UV ray resistant front allows barcodes to be scanned



Tough, transparent PVC profile in a choice of 4 heights supplied with aggressive high cohesion adhesive strip for permanent locations. Precut sizes from stock, special sizes up to 3m on request.

Material Specification

PVC Profile

Transparent profile extrusion – UV ray resistant – general purpose
Average thickness 25mm and 38mm = 0.6mm; 54mm and 80mm = 0.8mm

Adhesive Strip

Temperature resistance:
-30°C to 175°C
(when applied at ambient)

Hanging foam test... > 24h

Adhesion (cN/20mm)
2000...2B steel,
2000...PC, PVC, PMMA
1800...PET
1600...PP

Adhesive type	Modified acrylic	
Tape thickness (no liner)	0.220 mm	NITTO 01B
Release liner type/colour	Siliconised brown paper	
Release liner thickness/weight	0.075mm-85g/sqm	NITTO 01G-058
Carrier type	Polyester	
Unwind force	10cN/50mm	NITTO 35A
Release value	40cN/50mm	NITTO 37A
Adhesion to stainless steel	2000 cN/20mm	NITTO 15A
Cohesion to BA	1mm	NITTO 62A
Shear	580 N/sqcm	NITTO 73A (BA steel)

Application; the surfaces to be bonded must be free of dust, release agents or grease.