

HGV Wheel Guides

Guide your HGV trailers onto docks without clash of vehicle wheel rims



Features & Benefits



- Fabricated to safely & accurately guide trailers onto loading docks
 - Low-level - Double Deckers 150mm High
 - High-level - Artic Trailers 200mm High
 - Or - custom fabricated to your site specific requirements
- Leading ends fitted with diamond grade yellow reflectors
- Other options
 - Straight or Cranked
 - Cast-in specification
 - Yellow powder-coat finish
 - Extended length units

“New generation design to eliminate expensive damage to HGV trailer wheel rim”



Technical Specification



UK Manufacture

- Fabricated from circular hollow section steel
- Welded end caps
- Hot Dip Galvanised to BS EN ISO 1461
- Bolt-down to suitable concrete slab with M16 x 150mm floor anchors (4 per)
- Typical internal width for setting out 2600mm
- Part No.s
 - WG-150-BSG
Wheel Guide, bolt-down straight, galvanised (2000mm x 150mm High)
 - WG-150-BCG
Wheel Guide, bolt-down, cranked, galvanised (2000mm x 150mm High)
 - WG-200-BSG
Wheel Guide, bolt-down, straight, galvanised (2000mm x 200mm High)
 - WG-200-BCG
Wheel Guide, bolt-down, cranked, galvanised (2000mm x 200mm High)



Pedestrian Safety

Improve Safety For Your People



HGV Safety

Protect Buildings From Impact



Fork Lift Safety

Protect Equipment From Damage



Recycle Everything