



COBAdot

An easy to install rubber runner








- · Versatile rubber floor covering.
- Studded surface looks smart, while being a practical choice for both industrial and commercial buildings.
- Nitrile option recommended for oily, greasy or chemical-prone locations based on its resilient properties.
- Provides enhanced underfoot grip to reduce the risk of slipping.
- Ease of installation minimises any down time can be bonded or laid loose to the floor.
- This product is designed as a runner only as the dots may not match up when lengths are placed together.



Styles Available





Part Number	Size	Colour	Weight (kg)
CDN010001	1.2 m x 10 m x 3 mm	Black Nitrile	51
CDN010001C	1.2 m x per linear metre x 3 mm	Black Nitrile	4.5
CDN010002	1.2 m x 10 m x 4.5 mm	Black Nitrile	73.85
CDN010002C	1.2 m x per linear metre x 4.5 mm	Black Nitrile	7.38
CDN060001	1.2 m x 10 m x 3 mm	Grey Nitrile	51
CDN060001C	1.2 m x per linear metre x 3 mm	Grey Nitrile	4.5
CDN060002	1.2 m x 10 m x 4.5 mm	Grey Nitrile	73.85
CDN060002C	1.2 m x per linear metre x 4.5 mm	Grey Nitrile	7.38
CDS010001	1.2 m x 10 m x 3 mm	Black	45.45
CDS010001C	1.2 m x per linear metre x 3 mm	Black	4.54
CDS010002	1.2 m x 10 m x 4.5 mm	Black	80.35
CDS010002C	1.2 m x per linear metre x 4.5 mm	Black	7.8
CDS060001	1.2 m x 10 m x 3 mm	Grey	45.45
CDS060001C	1.2 m x per linear metre x 3 mm	Grey	4.54
CDS060002	1.2 m x 10 m x 4.5 mm	Grey	80.35
CDS060002C	1.2 m x per linear metre x 4.5 mm	Grey	7.8

Material	Standard - Natural/Synthetic rubber. Nitrile - Natural/NBR rubber.
Surface Finish	Studded
Product Height	3 mm, 4.5 mm
Roll Length	10 m
Min. Operating Temperature	-30°C
Max. Operating Temperature	+70°C
Resistance to Chemicals	Resistant to mild acids and alkalis
Environmental Resistance	Suitable for dry indoor environments
Typical Applications	Walkways
Installation Method	Loose laid or bonded to the floor surface
COO (Country of Origin)	CN/AE