



Deckplate Anti-Static

Hardwearing dual layer mat for static sensitive areas



- Hardwearing anti-fatigue mat for static sensitive areas.
- Conductive top surface protects operatives and components.
- Diamond pattern surface is attractive and slip resistant.
- Top surface provides resilience to many industrial chemicals.
- Grounded via a 10 mm male stud fitted to the mat.
- Supplied with ramped edges as standard to reduce the risk of trips.
- Tested to EN14041 resistance requirements.
- Rv: $9.8 \times 10^7 \Omega$



Parts

| Part Number | Size | Colour | Weight (kg) |
|-------------|--------------------------|--------|-------------|
| DPS010005 | 0.9 m x 18.3 m | Black | 108 |
| DPS010005C | 0.9 m x per linear metre | Black | 8 |
| DPS010007 | 1.2 m x 18.3 m | Black | 166 |
| DPS010007C | 1.2 m x per linear metre | Black | 9 |
| DPS010609 | 0.6 m x 0.9 m | Black | 3.54 |
| DPS010915 | 0.9 m x 1.5 m | Black | 8.86 |

Technical Specifications

| | |
|----------------------------|---|
| Material | Vinyl top surface with PVC foam backing (fusion bonded, not glued) |
| Surface Finish | Diamond pattern |
| Product Height | 14 mm |
| Min. Operating Temperature | 0°C |
| Max. Operating Temperature | +60°C |
| Resistance to Chemicals | The PVC top surface provides limited resistance to chemicals and oils |
| Environmental Resistance | Suitable for dry indoor environments |
| COO (Country of | CN |

Origin)

Guarantee

3 years when used in dry environment

Additional Information



Deckplate AS - ESD Test BS EN 14041

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com