



## Gripfoot

#### Improve grip on smooth surfaces with an abrasive grit finish

- Self-adhesive tapes, cleats or tiles with an abrasive grip surface which helps to improve anti-slip properties.
- A hardwearing and easy to install solution to help prevent slips and trips.
- Available in a range of colours, including a hazard version which provides high visibility in darkness and low light conditions.
- Gripfoot Tape versatile for floor surfaces, machinery and vehicles. •
- Gripfoot Cleats (rectangular) are designed for use on steps and stairs.
- Gripfoot Tiles (square) are ideal for increasing safety on smooth, tiled • floors.
- Slip tested to DIN 51130.



















Clear



### Parts

		Weight (kg)
25 mm x 18.3 m	Black	0.4
50 mm x 18.3 m	Black	0.8
102 mm x 18.3 m	Black	1.45
152 mm x 18.3 m	Black	2.5
140 mm x 140 mm	Black	
152 mm x 610 mm	Black	
50 mm x 18.3 m	Black/Yellow	0.8
50 mm x 18.3 m	Blue	0.8
50 mm x 18.3 m	Red	0.8
50 mm x 18.3	Red/White	0.8
50 mm x 18.3 m	Green	0.8
50 mm x 18.3	Yellow	0.8
50 mm x 18.3 m	Luminous	0.8
	50 mm x 18.3 m 102 mm x 18.3 m 152 mm x 18.3 m 140 mm x 140 mm 152 mm x 140 mm 50 mm x 18.3 m 50 mm x 18.3 m 50 mm x 18.3 m 50 mm x 18.3 m 50 mm x 18.3 m	50 mm x 18.3 m Black   102 mm x 18.3 m Black   152 mm x 18.3 m Black   140 mm x 140 mm Black   152 mm x 610 mm Black   50 mm x 18.3 m Black   50 mm x 18.3 m Black/Yellow   50 mm x 18.3 m Blue   50 mm x 18.3 m Red   50 mm x 18.3 m Green   50 mm x 18.3 m Green   50 mm x 18.3 m Yellow

# **Technical Specifications**

Material	Abrasive grit consisting of aluminium oxide bonded to a polymer substrate. Solvent based acrylic emulsion adhesive backing. Product supplied with a moisture resistant release liner.
Surface Finish	Grit
Product Height	1.05 mm
Min. Operating Temperature	-10°c
Max. Operating Temperature	+60°c
Environmental Resistance	Suitable for indoor environments
UV Resistance	Yes
Typical Applications	Stairs, Ladders, Ramps, Walkways, Vehicles

Part Number	Size	Colour	Weight (kg)	Installation Method	Self-adhesive tape applied with pressure
GF120002	50 mm x 18.3 m	Clear	1.45		
				COO (Country of Origin)	TW
				Adhesion Strength	1.6 kg / 25 mm
				Coating Thickness	0.05 mm
				Solvent Residue	0.50%
				Release Force	30g / 25 mm
				Slip Tested to	DIN 51130 - R13

#### Additional Information



Gripfoot Ramp Slip Test DIN 51130

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

vww.cobaeurope.com