





Modular anti-fatigue matting for larger areas











- Tiles link together to provide a very comfortable anti-fatigue surface.
- Can withstand temperatures of up to 160°C and spillage of molten glass.
- Individual tiles can be moved and replaced with ease.
- Fully slip tested see datasheet for details.
- Main tiles available in two options: Standard or Nitrile / B1
- Nitrile option has excellent resistance to oils, chemicals and grease.
- B1 version tested to BS EN 13501 see datasheet for details.
- Optional ramped edging in yellow or black.



Parts

Part Number	Size	Colour	Weight (kg)
ST010001	0.9 m x 0.9 m	Black	10.5
ST010001B1	0.9 m x 0.9 m	B1 Nitrile	10.5

Technical Specifications

Material	Standard - Natural rubber with 20% NBR. Nitrile version - 35% NBR.
Surface Finish	Solid textured
Product Height	18 mm
Min. Operating Temperature	-20°C

Max. Operating Temperature	+130°C
Resistance to Chemicals	Standard version offers limited resistance to chemicals and oils. Nitrile version offers excellent resistance to oils and chemicals.
Environmental Resistance	Suitable for wet and dry environments. Will withstand welding splatter and spillages of other hot materials.
UV Resistance	Yes
Typical Applications	General industrial
Installation Method	Loose lay interlocking tiles
Accessories	Bevelled corner edges
Cleaning Method	Use of hard detergents not recommended
Fire Tested to	B1 version: BS EN 13501-1 Class Bfl - s1
COO (Country of Origin)	IN
Storage and application	Store at room temperature, free from deformations.
Tensile Strength	3.5 to 4 MPa
Notes	Silicone is used in the production process of the mats and a residue will possibly be left on the mat. This can be washed off using hot soapy water
Slip Tested to	DIN 51130 - R10

Additional Information



Installation Guide



Solid Fatigue Step B1 Fire Test BS EN 13501



Solid Fatigue Step B1 Fire Test EN ISO 11925



Solid Fatigue Step Ramp Slip Test DIN 51130



Solid Fatigue Step B1 Fire Test EN ISO 9239