

# **GRP Stair Tread**

### **Short Description**

Stair tread covers are ideal for use in any high traffic area, helping to minimise the risk of slips, trips and falls. Designed for new projects and refurbishments, the simple design allows for quick and easy installation, ensuring limited downtime and disruption. All our stair tread covers are manufactured from high quality fibreglass, ensuring longevity and maximum protection.

## **Product Images**









### **Description**

- Moulded fibreglass stair tread cover with 87° degree angle and flat cover plate.
- Robust construction to withstand heavy usage and harsh environments.
- Impregnated silica grit surface protects against delamination a common problem with metal backed alternatives.
- Fire-retardant additives ensure excellent fire and heat resistance, conforming to ASTM E84.
- Overall 4mm thickness.
- Available in bespoke lengths up to 3m, with additional options of drilling and countersinking.
- Available in cut to size to suit any tread depth, length or shape.

#### **Additional Information**

**Specifications** 

**Wear Resistant** Wear resistant surface to Level 3

**Slip Resistance** Slip resistance Level 3

**Chemical Resistant** Chemical resistant

Flame Retardant Flame retardant

**Outdoor** Suitable for outdoor use

**Dry Area** Suitable for use in dry areas

**Grease Area** Suitable for use in greasy areas

**Heavy Areas** Suitable for use in heavy use areas

Oil Area Suitable for use in oily and greasy areas

**Wet Area** Suitable for use in wet areas

#### **Environment**

**Dry Zone** Dry Zone

Wet Zone Wet Zone

Oily/Greasy Zone Oily/Greasy Zone

Chemical Zone Chemical Zone

#### **Tests**

- Pendulum Test Value (PTV), Dry 82, Wet 76
- Ignitablity, tested to EN ISO 9239-1: 2010
- Radiant panel test for floorings, tested to EN ISO 9239-1
- Anti-slip, tested to BS7976.2
- ASTM E84

## **Product Options**

Colour:	Black
	Black/White
	Black/Yellow
	Yellow
Width:	55mm x 220mm
	55mm x 345mm
Length:	1m
	2m
	3m