

# Harness PIONEER™


RESCUE / CONFINED SPACE

## TECHNICAL SPECIFICATION

HEIGHT SAFETY

The Pioneer™ range has a two tone colour scheme to help the user in donning and inspection. Along with light alloy steel hardware makes this a comfortable day to day product.

FAR0205



### METAL COMPONENTS

Material: High strength steel.

Finish: Deburred & polished.

### DIMENSIONS

Size: Universal.

Weight: 1690 g (+ 10 g).

### STITCHING THREAD

Material: High-tenacity polyester.

### CLEANING & MAINTENANCE

Maintenance of this product must only be carried out by a trained and competent person who will:

Clean the product using the following procedure: using only warm water, using only mild detergent, using only a sponge or soft nylon brush, using fresh clean water to rinse the detergent off the product, drip dry the equipment allowing the product to thoroughly dry out before next use.

Ensure that the following cleaning methods are NOT used: water over 40°C, bleach, any detergent not suitable for bare skin, wire brushes or other scouring agents, jet wash or other power products, radiators or other direct heat sources, ensure that a thorough visual and tactile examination of the product is made after cleaning, before the item is allowed to be re-used.

### WEBBING

Material: Polyester.

Width: 44±1 mm.

Breaking strength: 25 kN.

### CHARACTERISTICS

One dorsal attachment D-ring for fall arrest with extension.

One front D-ring for fall arrest.

One overhead D-ring for rescue with extension strap.

Adjustable shoulders, chest and leg straps.

Quick release buckles.

Plastic retainers to keep straps tidy. Sub-pelvic strap.

Fall indicator for easy inspection.

2 colours for easy donning.

Labels of inspection and instructions protected in a black PVC pouch.

### CONFORMITY

EN 361: 2002 & EN 1497: 2007 Rated to 140 kg.

The lifespan of the product is 10 years from the date of manufacture subject to passing necessary checks and inspection by a competent person.

Static strength: 15 kN for 3 min at each attachment element.

Dynamic strength: Free fall from 4 m height donned to a test dummy weighing 100 kg at each attachment element.

DISCLAIMER: Information presented within this technical specification was correct on date of issue. Information may be subject to change without notice as part of ongoing product improvement and development. To confirm any specific piece of information shown is current please email [technical@jpsafety.com](mailto:technical@jpsafety.com).



MANUFACTURING FOR SAFETY  
[WWW.JPSAFETY.COM](http://WWW.JPSAFETY.COM)

UKSALES@JSP.CO.UK  
TEL: +44 (0)1993 826050



Issued 08/06/2021-2