Self Retractable Lifeline

One of the ligthest in its class.

HEIGHT SAFETY

SPECIFICATION

TECHNICAL

FAR0701



DIMENSIONS

Length: 2 meters

Weight: 848.5 g (+- 20 g)

CLEANING & MAINTENANCE

In case of minor soiling, wipe the equipment with a cotton cloth or soft brush. Do not use any abrasive material. For intensive cleaning wash in water at a temperature between 25°C to 50°C using a neutral detergent. It should be allowed to dry by itself and be kept away from open fires/ flames or any other source of heat. Avoid direct sunlight.

The user should carry out a pre-use check of the Self Retractable Lifeline, to ensure that it is in a serviceable condition and operates correctly before it is used.

The pre-use check shall involve checking of any wear or abrasion on wire ropes/webbing and sign of corrosion if any on metal parts or any breakage of the casing.

- Width: 21 mm
- Minimum Breaking strength: 20 kN

CHARACTERISTICS

Robust and durable plastic casing.

- Webbing width 21 mm with shock absorber.
- wooning wider 21 min with Shock absolute
- 2 quarter turn gate aluminium connector on both ends.

Gate opening: 21mm. Conforms to EN362:2004 Class B.

CONFORMITY

EN 360: 2002 Rated to 140 kg (vertical use)

The lifespan of the product is 10 years from the date of manufacture subject to passing necessary checks and inspection by a competent person. Horizontal use (Sharp Edge VG 11 RFU CNB/P/11.060), fall factor 2 use in the limit of 100 kg.

Static strength: 15 kN for 3 min

Dynamic strength: 100 kg mass free fall with the breaking force of less than 6 kN & arrest distance less than 2 meters.



UKSALES@JSP.CO.UK TEL: +44 (0)1993 826050



